

# Wireless Transmission System

## BACKGROUND OF THE INVENTION

5

### 1. Field of the Invention

10 This invention relates to a wireless transmission system, more particularly, to a wireless transmission system, which is used in the foundation. The present invention uses the first wireless network interface, which is assembled in a mobile computer and the second wireless network interface, a microprocessor, and a bridge which are assembled in the foundation so the mobile computer can control the devices, which are connected with the foundation, by using wireless  
15 controlling.

### 2. Description of the Prior Art

20 Computers have become indispensable tools in the present day and age. No matter if its leisure time or work, the computer plays the important role to conform to the needs of the users. The computer is also the best tool to save data or information. They can be used to classify data or information systematically by using a controlled program to retrench the waste of labor and power and to increase the efficiency of  
25 the work. The computer further reduces the time spent in searching for the users needed information by quickly using the programs to the efficiency, which is paid much attention in our present society.

Following the needs of users, the mobile computers, such as: notebook and personal digital assistant (PDA) are used in general. But in order to reduce the volume and the weight of mobile computers, the mobile computers usually reduce several devices, which are not usually used by the users. The reduced devices are assembled in the foundation to make the users use these reduced devices following the needs of the users.

Each different kind of the mobile computer has different reduced devices. Therefore, the foundations, which are used to collocate to the different mobile computers, are different, such as the dock, which is used to collocate the notebook. But the objective of using different foundations is the same to expand the functions of the mobile computer. The mobile computer, whose volume and weight are reduced, will not loose the partial functions of the desk computer by using its foundation. The mobile computer will also not cause any inconvenience or reduce the working efficiency of the users.

In general, the foundations have a peripheral component interconnect (PCI) device, integrated drive electronics (IDE) device, and a network device to connect to the outside apparatus, such as a printer, a scanner, a magnetic disk, or a modem. When the mobile computer is connected with the foundation, the mobile computer can bring its functions into full play. When the users connects the mobile computer with the foundation, the users can control the peripheral of the foundation by using the mobile computer and the mobile computer can reach the functions of the desk computer. Therefore, the connected interface between the mobile computer and the foundation is very

important.

The traditional way to connect the mobile computer with the foundation is usually by a connector or a transmission line. The signals of the mobile computer are transmitted to the bridge, which is in the foundation, by using a transmission line or a connector. After the bridge, deciding the types and the address of the signals, the bridge will transmit the peripheral component interconnect device. The integrated drive electronics device, and the network device to drive the peripheral of the foundation and to complete the command, which is typed by the users from the mobile computer.

Although the volume and the weight of the traditional mobile computer has been reduced, the functions of the mobile computer comparing to the functions of the desk computer are reduced the partial functions. If the users want to make the functions of the mobile computer reach to the functions of the desk computer, the users must connect the mobile computer with the foundation. In the present technology, the traditional foundation must use the transmission line or the connector to connect with the mobile computer. This condition is very inconvenient for the users and will decrease the convenience and the mobility of the mobile computer. Therefore, using the traditional foundation and the mobile computer can not increase the working efficiency of the users and will only increase the problems the users will encounter.

There are many pins in the connector, which is used to connect the traditional foundation with the traditional mobile computer. If the

pins are inserted in the wrong locations, the mobile computer can not be connected with the foundation successfully and the mobile computer and the foundation are damaged more easily. If several pins are broken, the users must pay more fees to repair the damaged pins and the cost of the users may be increased. If the users use the transmission line to connect the traditional foundation with the mobile computer, the mobile computer and the traditional foundation will not be connected with each other because the connector of the transmission line may be come off and the inner lines of the transmission line may be broken to trouble the users.

## SUMMARY OF THE INVENTION

In accordance with the above-mentioned invention backgrounds, using the traditional transmission line or the connector to connect the mobile computer and the foundation will cause the inconvenience of the users and will cause damage to the hardware. The present invention provides a system to provide a more convenient interface for the users by using a wireless transmission way to connect the mobile computer with its foundation.

The second objective of this invention is to increase the efficiency of the mobile computer and the foundation by using the wireless transmission to connect the mobile computer with its foundation.

The third objective of this invention is to extend the lifetime of the mobile computer and the foundation by using the wireless

transmission way to connect the mobile computer with its foundation.

The fourth objective of this invention is to reduce the rate of damages the mobile computer and foundation sustains by using the wireless transmission to connect the mobile computer with its foundation.

The fifth objective of this invention is to reduce the cost of damages the user pays by using the wireless transmission to connect the mobile computer with its foundation.

The further objective of this invention is to increase the efficiency by using the wireless transmission to connect the mobile computer with its foundation.

In accordance to the foregoing objectives, the present invention provides a system that is more convenient for the users by using a wireless transmission to connect the mobile computer with its foundation. The present invention assembles the first wireless network interface in the mobile computer and assemble the second wireless network interface, the microprocessor, and the bridge in the foundation to make the data being transmitted between the mobile computer and the foundation in the wireless transmission way. The present invention can also increase the efficiency of the users, the mobile computer, and the foundation and extend the lifetime of the mobile computer and the foundation. The present invention can further reduce the rate of damaging the mobile computer and foundation and reduce the damaged cost of the users.

## **BRIEF DESCRIPTION OF THE DRAWINGS**

In the accompanying drawing forming a material part of this  
5 description, there is shown:

Fig. 1 shows a system diagram of the present invention; and

Fig. 2 shows a proceeding diagram of using the present  
10 invention system in the mobile computer.

## **DESCRIPTION OF THE PREFERRED EMBODIMENT**

The foregoing aspects and many of the attendant advantages of  
15 this invention will become more readily appreciated as the same  
becomes better understood by referring to the following detailed  
description, when taken in conjunction with the accompanying  
drawings, wherein:

20 Following the advancements of science and technology, the  
dependence of the user upon the server has become higher and higher.  
But the volume and weight of the desk computer has increased along  
with these advancements. Therefore, the desk computer is suited for a  
fixed location. The rate of data transmission the mobile computer can  
25 receive has become faster and allows the users to gradually get the  
information conveniently and quickly. In order to reduce the volume and  
the weight of the mobile computer, the mobile computer usually  
decreases partial functions of the desk computer to remove several

devices and to reach the main objective of the mobile computer by reducing the volume and the weight. For the users, sometimes the partially decreased functions of the mobile computer are still to be desired. Therefore, all kinds of mobile computers have its foundation to expand the scope of the mobile computers.

However, following the kinds of the mobile computers are different, every kind of the mobile computer has its own foundation. No matter what kind of mobile computers, if the users want to connect to the mobile computer and the foundation with each other, the users must use the transmission line or connector to connect to the mobile computer with the foundation to expand the functions of the mobile computer. But these kinds of connections can decrease the convenience of the mobile computer and cause damage to the mobile computer and the foundation more easily. Therefore, the present invention must be used to connect the mobile computer and the foundation with each other by using wireless transmissions. If the mobile computer needs to be charged, the users still use the transmission line or the connector to connect the mobile computer and the foundation to get electric power.

The first wireless network interface is assembled in the mobile computer at first in the present invention to allow the mobile computer to send and receive the wireless signals. In the present invention, the standard wireless protocol of the first wireless network interface, which is in the mobile computer, is IEEE802.11; this kind wireless protocol will not limit the scope of the present invention. Then the second wireless network interface, a microprocessor, and a bridge are assembled in the foundation. In the present invention, the standard wireless protocol of

the second wireless network interface, which is in the foundation, is IEEE802.11 and this kind of wireless protocol will not limit the scope of the present invention. The wireless protocol of the first wireless network interface and the wireless protocol of the second wireless network interface must be the same to send and to receive the wireless signals, which are sent from another, mutually. If the wireless protocol of the first wireless network interface and the wireless protocol of the second wireless network interface are different, the mobile computer and the foundation will not send and receive the wireless signals; which are sent from another, mutually to cause the failure in connecting with the mobile computer and the foundation. The driver of the first wireless network interface must be installed in the operating system (OS) of the mobile computer to make the mobile computer send and receive the wireless signals successfully.

If the data needs to be transmitted from the mobile computer to the foundation by using the present invented system, the data will be transformed to wireless signals by using the microprocessor, which is in the mobile computer at first. Then the wireless signals will be sent out by using the first wireless network interface, which is in the mobile computer. Within the fixed distance, after the wireless signals are sent from the mobile computer; they are received by the second wireless network interface, which is in the foundation. These wireless signals will be transmitted to the microprocessor, which is in the foundation, to be transformed by the type of the wireless signals. The objective of the microprocessor, which is assembled in the foundation, is to transform these types of signals. The microprocessor of the foundation will transform the wireless signals, which are transmitted from the second



wireless network interface, to become the signals, which can be received by the devices that are assembled in the foundation or are connected with the foundation. The wireless signals are the parallel signals and the signals that can be received by the devices that are assembled in the foundation or are connected to the foundation, are the serial signals in general. Therefore the microprocessor is used to transform the types of signals to make the connection from the mobile computer to the foundation simply and successfully.

After the wireless signals are transformed to become the serial signals by using the microprocessor, the serial signals are transmitted to a bridge. The objective of the bridge, which is assembled in the foundation, is to transform a computer system input/output interface to other input/output interfaces. Therefore, the bridge, which is in the foundation, can transmit a signal to an input/output interface by judging the subject matter of the signals that are sent from the mobile computer.

In general, the foundation, which is connected to the mobile computer, is connected with others peripheral devices, such as a printer, scanner, and magnetic disk to increase the efficiency of the mobile computer and bring it into full play. After the peripheral devices receive the signals, which are transmitted from the mobile computer, by the input/output interface, the peripheral devices proceed the processes suddenly and transmit the signal back. The sending of data and address of the signal are transformed to the computer system input/output interface by using the bridge and are then transmitted to the microprocessor to transform the type of signal. The microprocessor



a wireless signal and the wireless signal will be sent by the first wireless network interface, which is in the mobile computer. When the second wireless network interface receives the wireless signal, the electric power-saving state will be closed and the power of the foundation will be opened automatically to proceed with the command of the user. The users can depend on their needs to use the peripheral devices, which are connected with the foundation or in the foundation, to complete the work quickly and conveniently. This electric power-saving device of the foundation will reduce the cost to the user.

Each foundation, which is assembled with the present system, will send out the location through a wireless signal in a period time; no matter if the foundation is in the electric power-saving state or not. The wireless signals, which are sent from different foundations and locations, will not interfere with each other. After installing the driver of the first wireless network interface in the operating system of the mobile computer, the first wireless network interface will detect the location signals, which are sent from the foundations. When the first wireless network interface detects or receives the location signals, which are sent from the foundations, the driver will show the message that express' the mobile computers detection of the foundation to be used nearest its location, on the monitor of the mobile computer. If the mobile computer detects several foundations, the mobile computer will assign the numbers to the several foundations and will show the results on the monitor of the mobile computer to provide the choices and the uses for the users.

The wireless signal has it own scope of sending. This scope will

be increased or decreased following the different types of the wireless signals. Therefore, the users can choose the mobile computer and the foundation, which are produced by using the present invention system, following the different needs of the users. In general, most of the wireless transmission means that the wireless signals must be transmitted in the straight-line way. If there is an obstacle object between the wireless signal-sending end and the wireless signal-receiving end, the wireless signal will be broken easily. The wireless signals, which are used in the present invention system, have higher power to go through common domestic objects. If the mobile computer is in the scope of the wireless signals, the mobile computer can send or can receive the wireless signal and the functions of the mobile computer will not be limited to the locations of the foundation. The wireless transmission system of the present invention can also avoid damage to the mobile computer and the foundation when the users connect the mobile computer with the foundation by using the transmission line or the connector without caution. The present invention can further extend the lifetime of the mobile computer and the foundation.

Referring to Fig. 1, this shows a system diagram of the present invention. When the user types the command into the mobile computer 10, the command will be transformed to become a wireless signal and the wireless signal will be sent by the first wireless network interface 12, which is in the mobile computer 10. After the second wireless network interface 21, which is in the foundation 20, receiving the wireless signal, the wireless signal will be transformed to become a signal, which can be received for the devices that are connected with the foundation 20, by a microprocessor 22. Then the transformed signal will be transmitted into



the first wireless network interface does not detect the wireless signal location, the operating system will start to be executed 33. When the operating system of the mobile computer starts to execute, the operating system will detect the flag, which is build in the basic input/output system or not to express the mobile computer to be connected with the foundation or not 34. If the operating system has detected the flag, a sign will appear on the monitor of the mobile computer 35 to tell the users that the mobile computer is connected with the foundation. If the operating system has not detected the flag, the sign will not appear on the monitor of the mobile computer 36 to tell the users that the mobile computer is still not connected with the foundation.

In accordance with the present invention, the present invention provides a system to provide the more convenient using interface for the users by using a wireless transmission to connect the mobile computer with its foundation. The present invention assemble the first wireless network interface in the mobile computer and assemble the second wireless network interface, the microprocessor, and the bridge in the foundation to make the data being transmitted between the mobile computer and the foundation in the wireless transmission. The present invention can also increase the efficiency of the users, the mobile computer, and the foundation and extend the lifetime of the mobile computer and the foundation. The present invention can further reduce the rate of damaging the mobile computer and foundation and reduce the damaged cost of the users.

Although specific embodiments have been illustrated and described, it will be obvious to those skilled in the art that various

modifications may be made without departing from what is intended to be limited solely by the appended claims.

090805-11304  
090805-11304